

EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/4109/162/09/20/2284

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment:

QINGDAO WISDOM SAFETY PRODUCTS CO., LTD Manufacturer:

NO.45 BEIJING ROAD, BONDED PORT DISTRICT 266555 QINGDAO

Description

PPE Type: protective glove against mechanical risks

Product reference: WS-415

Article code:

Glove description: 13 GAUGE POLYESTER LINER WITH NITRILE SANDY COATED GLOVES

Available sizes: 7-12

Pictures:









ADD: NO. 45 BEIJING ROAD, BONDED PORT DISTRICT 266555 QINGDAO SHANDONG CHINA

Reference standard:

Levels of performance / class of protection

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material. « 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

EN ISO 21420:2020

EN 388:2016 + A1:2018

4121X

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 01 dated from SEPTEMBER 2020

NOTA: Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by Didier GUISADO

Certification and Quality Manager

Date of first issue: 02 September 2020 End of validity date: 02 September 2025







In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC

www.ctcgroupe.com

cemarking@ctcgroupe.com CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France

cofrac

QINGDAO WISDOM SAFETY PRODUCTS CO., LTD

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product : WS-415

Article code : /

Technical file index : 01

Last update : SEPTEMBER 2020

IDENTIFICATION

Reference of the product: : WS-415

Article code: : //

Basic Model

Technical file index: : 01

Last update : : SEPTEMBER 2020

Manufacturer:

QINGDAO WISDOM SAFETY PRODUCTS CO., LTD NO.45 BEIJING ROAD,BONDED PORT DISTRICT 266555 QINGDAO SHANDONG CHINA

tel: 86 133 4639 5329

fax:

Factory:

QINGDAO WISDOM SAFETY PRODUCTS CO., LTD NO.45 BEIJING ROAD,BONDED PORT DISTRICT 266555 QINGDAO SHANDONG CHINA

tel: 86 133 4639 5329

fax:

GLOVE DESCRIPTION

General glove description:

13 GAUGE POLYESTER LINER WITH NITRILE SANDY COATED GLOVES

This glove is designed against mechanical risks.

Type of coating finish: sandy

Visual description (picture back and palm sides):



Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)				
		Applicable	Covered by	
§1	Requirements defined in the Annex II §1 are applicable to all PPE	V	☑ Standard	
			☑ Instruction for use	
			☑ Marking	
§1.4	Manufacturer's instructions and information is available	V	☐ Standard	
			☑ Instruction for use	
			☐ Marking	
	PPE which may be caught up during use	>	☐ Standard	
§2.5			☑ Instruction for use	
			☐ Marking	
	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	V	✓ Standard	
§2.12			☑ Instruction for use	
			✓ Marking	
§3.3	The PPE is intended to protect against mechanical injuries	V	✓ Standard	
			☑ Instruction for use	
			✓ Marking	

Glove constitution:

	Reference	Color	Material	Surfacic mass (g/m²)	Gauges	Thickness
Palm		Black	Nitrile			0.5mm
Paim		Grey	Polyester	164g/m ²	13Gauges	
Back		Grey	Polyester	164g/m ²	13Gauges	
Cuff		Grey	Polyester/elastic	260g/m ²	13Gauges	
Binding		Brown	Polyester			-

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425. This glove is designed against mechanical risks. It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420:2020

Dexterity: 5
Available size range: 7-12

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

- « X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
 - « 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388 : 2016 + A1 : 2018

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm

TEST REPORTS

Laboratory	CTC	Other
	S200707587_1 S200707586_1(DMFU) S200707592_1	
EN 388	S200707587_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer:

Logo (€

Glove's reference: WS-415

Article Code:

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer:

Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example:



ADD: NO. 45 BEIJING ROAD, BONDED PORT DISTRICT 266555 QINGDAO SHANDONG CHINA

Method of marking on the glove :

screen printing/back of gloves

Packaging:

12 pairs/dozen/polybag, 240 pairs/carton

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Cleaning:

The gloves are not washable.

MEANS OF CONTROL

- 1. All inspection processes including sewing, moulding and all incoming raw meterials are based on random acceptance sampling.
- 2. Goods Inwards Q.C. inspect and check all raw meterials before releasing to Production Dept.
- 3.Production/Q.C. Dept. perform on-line checking on sewing machine floor for based on EN420 sizing standard.
- 4.Q.C. Dept. perform size and label checks before forwarding to Moulding Dept.
- 5.Moulding/Q.C. Dept. will undertake finial inspection tests for size, weight chemical testing and cutting/abrasion according to EN388Standard and send to CTC for test EN388,EN420..each year.
- 6. Packaging checks are performed by Q.C. before shipment.
- 7.All reject materials are inspected and either disposed of responsibly or re-worked responsibly within the production process.

INSTRUCTION FOR USE

QINGDAO WISDOM SAFETY PRODUCTS CO., LTD

NO.45 BEIJING ROAD, BONDED PORT DISTRICT 266555 QINGDAO SHANDONG

CHINA

Glove reference: WS-415

Article code: /
User notice index: 01

Last update: SEPTEMBER 2020

WS-415 EN388 XXXXXX EN388

ADD: NO. 45 BEIJING ROAD, BONDED PORT DISTRICT 266555 QINGDAO SHANDONG CHINA

Glove description :

13 GAUGE POLYESTER LINER WITH NITRILE SANDY COATED GLOVES

This is a Personal Protective Equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425 applicable from April 21th, 2018: innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075) 4, rue Hermann Frenkel 69367 LYON Cedex 07 FRANCE

Applicable standards :

The glove meets the requirements of the standard EN ISO 21420 : 2020 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available Size Range: 7-12

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B.

Moreover, this glove has been designed for the following applications :

- « X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
 - « 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Application :

Mechanical hazard - EN 388:2016 + A1:2018



4 1 2 1 X Levels of performance



Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	2	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

Read carefully the instructions for use provided with the product

Protection limit:

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

No flame protection is claimed. This glove shall not be in contact with naked flame.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer. The levels of performance against mechanical risks mentioned are only valid for the palm of the glove (except Impact protection).

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity:

Available with product.

Available on : www.wisdomsafety.com